

Halsted Seating

Technical Specifications

Construction & Materials

- Seat/Back:** High Grade Polyurethane Foam, 2" thick in the seat and 1 ½" thick in the back. Textiles are sewn with double stitch seams. High quality sinuous springs with weight distribution rods ensure a comfortable seating application.
- Frame:** Exposed wood components and chair frame are manufactured using European Beech and are free of spirits, discoloration, pits, shakes, and wormholes. All chair joints are double-doweled or mortised and tenoned, screwed, and glued for maximum strength and durability. All seats feature corner blocking. Frames are individually hand assembled and sanded prior to being finished. Non-marring nylon glides included in each leg at floor level.
- Finish:** A multi-step, hand-finishing process on all exposed wood frames. Chairs feature a catalyzed varnish finish which offers durability, lasting beauty, and resistance to normal wear.

Features


- Carved arm accents and optional button tailoring make Halsted a handsome and versatile addition to office, lounge, or conference environments.
- Choose from standard upholstered or button-tufted back styles.
- Select caster models for easy mobility-available in brass (standard) or silver hooded wheel casters. For models with glides, select nylon (standard) or felt glides.
- Available in single upholstery in a wide variety of graded-in or contract options, including fabric, vinyl, and leather. Find inspiration at www.indianafurniture.com/resources/textiles.
- Choose from 28 wood finishes for the frame. Find inspiration with our [Surface Material options](#).
- Ships fully assembled.

Certifications & Compliance


- Seat and back comply with CAL 117-2013
- Intertek Sustainability Certified for compliance with VOC emission concentrations
- BIFMA level® Certified for environmentally-preferable and socially-responsible office furniture
- BIFMA Compliant® Certified for meeting mechanical standards that focus on safety and durability
- TSCA Title VI (Formerly CARB) Compliance
- Contribution to U.S. Green Building Council's LEED Program

Dimensions


Seat Width	19"	Seat Depth	16½"	Seat Height	17"	Ship Wgt	32lbs	Cubes	16.9
Chair Width	23½"	Chair Depth	23"	Chair Height	32"	Arm Height	26"		




166TB



168TB



166



168

