

### General Information

---

- Solutions for Single User, Multiple Users & Collaboration Areas.
- Assembled and modular components maximize customization and functionality.
- 22 Woodgrain and Solid Laminates, 4 High Gloss Acrylics, 16 Pulls and 4 Edge options.
- Worksurfaces are fully supported by floor supported pedestals or legs.
- The placement of pedestals or legs will not interfere with the clearance of the kneespace.
- All hardware necessary for proper installation and stability of an item is provided.
- All hardware on a unit is concealed.
- NEMA Plug, Hardwired and Daisy Chain Power/Data Grommets are available in a variety of configurations.
- Custom capabilities.

### Worksurface Construction

---

- Worksurfaces are 1" thick thermally-fused laminate (TFL) or high pressure laminate (HPL) using 3mm matching PVC rims on profiled edges and 1 mm matching PVC rims on self edges.
- Worksurfaces and tops on casegoods less than 65"H are constructed with a Grade M2 particleboard core 45 lb. medium density fiberboard core with thermally-fused laminate (TFL) or high pressure laminate (HPL) on exposed face and a black backer sheet on all unexposed faces.
- Tops on casegoods greater than 65"H are constructed with a Grade M2 particleboard core 45lb. medium density fiberboard core with thermally fused laminate on both faces.
- Worksurfaces are bonded to the core with a PVA adhesive in a cold press to prevent separation of the laminate from the core.
- Worksurfaces are securely fastened together using high quality European style fastening systems and heavy-duty 16-gauge joining brackets and wooden dowels to assure maximum strength.
- Primary worksurfaces are profiled on approach and user sides; Secondary worksurfaces are profiled on user side only.
- Grain direction runs left to right unless noted in Price List.
- Worksurfaces fit flush with adjoining worksurfaces.
- Returns & Bridges ship with flat brackets & screws to attach to adjoining worksurfaces.
- Grommets available for worksurfaces are 2 3/8" in diameter, have a low profile, and include an insert and cover.
- Grommets can be field or factory installed.
- Factory installed grommets may be ordered in the worksurfaces of desks, returns, bridge units and credenzas.

### Drawer Construction

---

- Drawers are 1/2" thick wood grain vinyl wrapped construction with mitered corners and a 3-ply, 3/4" thick drawer front, thermally fused laminate on both faces with matching PVC edge band on all edges.
- Drawer fronts have vertically matched grain.
- Drawers are 5-sided construction which allows for easy removal of the drawer fronts without disturbing the contents of the drawer.
- Box and file drawers have 1/8" thick hardboard bottoms with a vinyl face.
- Lateral file drawers feature 1/4" thick bottoms with a vinyl face.
- Drawer bottoms are placed in a Dado groove reinforced with hot melt glue that provides a consistent structure along the entire length of all sides of the drawer bottom.
- Box and file drawers have full extension, progressive action slides with precision steel ball bearings.
- All desks have a black utility tray in the box drawer.
- All suspensions have a lifetime warranty.
- File drawers have full height sides and metal file rails.
- A single lock core locks all drawers within a pedestal or lateral file.
- Legal width file drawers provide legal filing front to back, and letter or legal filing side to side.
- Letter width file drawers provide letter filing front to back, and letter or legal filing side to side.
- All file drawers are standard with custom fitted filing systems designed to accommodate a variety of filing requirements.
- The custom fitted filing systems prevents folders from binding and allows the drawer to close with index tabs in place.

## Component Construction

---

- TFL chassis and storage components are securely fastened together using high quality European style fastening systems and heavy-duty 16-gauge joining brackets and wooden dowels to assure maximum strength.
- Casegood components are constructed with a Grade M2 particleboard core with thermally fused laminate on both faces.
- All units feature leveling glides with 1¼" of adjustment.
- Exposed edges have matching PVC edge band.
- Back panels on all units are inset into the sides so no raw edges are visible.
- All desks, non-lateral credenzas, and returns have wire management access from pedestal to kneespace.
- Modesty panels are available on returns.
- L-support panels offer support for worksurfaces without modesty panels.
- Hinges on all doors are soft close, concealed and open 100 degrees.
- The height from the worksurface to the bottom of a surface mounted hutch is 23¾".
- Lateral File cabinets are equipped with an anti-tilt system which only allows one drawer to open at a time.
- Lateral file and hybrid storage cabinets are standard with central locking. Only one lock is required to lock all drawers. Door will have a separate lock that will match the drawers.
- Doors on media cabinets for video screens or TV storage have hinges that allow the doors to open fully for unobstructed viewing of the screen.
- Units with shelves are adjustable in 1¼" increments.
- Wardrobe cabinets that are 24" deep allow sufficient room to use standard coat hangers.
- Wardrobe and storage cabinets are the same height as a desk/return/credenza with a hutch.
- Drawer and Door fronts have vertically matched grain and utilize the same drawer construction as the pedestals.
- Doors are available in laminate, metal framed frosted acrylic, dry erase board & high gloss acrylic options.
- All desks, credenzas, returns, and files feature standard locking.
- Removable lock cores allow for re-keying in the field.
- All units ship randomly keyed standard, keyed alike available on request.
- Lock cores match pull color (silver or black).
- Route power and data cables away from the worksurface through inherent grommet placement.
- Grommets will be black or silver based on pull color selected.
- Undersurface tracks are available for additional cord management.
- Above/Below Privacy Screens in TFL, Tack Board, High Gloss Acrylic & Frosted Acrylic.
- Modesty & Privacy Panels available in various heights in TFL, High Gloss Acrylic & Frosted Acrylic.
- Gallery Screens are available in Straight and L-Configurations to wrap desks for privacy.
- Component Cushions can be added to low storage components to create seating in a variety of spaces.
- All units have a minimum of 4 adjustable glides with an adjustment from the floor of 1¼".

## Tack Boards

---

- Tack Boards are available in a wide variety of fabric selections for all hutch sizes.

## Power & Data

---

- Duo Bezel Unit
  - › Recesses into worksurface for easy access to power and data.
  - › 2 power/2 USB ports.
  - › Independent USB circuit controllers deliver up to 2.1 amps to each post.
  - › All mounting hardware included.
  - › FCC Part 15A and UL Approved for horizontal and vertical applications.
  - › NEMA Plug units include a 10' Power Cord.
  - › Hardwired units are 8 Wire/4 Circuit; Maximum 10 Duo units per circuit.
  - › Daisy Chain units allow up to 8 modules to be connected with available jumper cord.

## Power & Data (cont.)

---

- Trio Bezel Unit
  - › Recesses into worksurface for easy access to power and data.
  - › 3 power/2 USB/1 Open Data Port.
  - › HDMI, VGA, or RJ45 Accessories sold separately.
  - › Independent USB circuit controllers deliver up to 2.1 amps to each post.
  - › All mounting hardware included.
  - › FCC Part 15A and UL Approved for horizontal and vertical applications.
  - › NEMA Plug units include a 10' Power Cord.
  - › Hardwired units are 8 Wire/4 Circuit; Maximum 10 Duo units per circuit.
  - › Daisy Chain units allow up to 8 modules to be connected with available jumper cord.
- Power Data Port
  - › Flip Top design retracts into worksurface to regain productive space.
  - › One-Touch access to power and data.
  - › (2) Power Outlets and (2) Open Ports for Data.
  - › Water-Proof simplex outlets.
  - › Includes a Voice/Data adapter kit to accept couplers and jacks when required.
  - › 6' Power Cord.
- Chargespot
  - › Wireless Charging Enabled Devices (Qi) can be used directly with ChargeSpots without the Aid of a Spark.
  - › Not Compatible with Metal or Glass Surfaces.
- Chargespot Spark
  - › Apple Lightning compatible with Apple iPhones 5 and above.
  - › Micro USB Compatible with Android, Windows and Blackberry Phones.
  - › USBC are for newer Android Phones.

## Task Lighting

---

- Tasklights are available for factory or field installation.
- Tasklights are concealed by a valance.
- Tasklights are available in various sizes to match the length of the hutch.
- LED light.
- Tasklights have a lens cover to reduce glare.
- Tasklights have an easily accessible on-off rocker switch.
- Jumper cords and occupancy sensors available.
- ETL listed and labeled.
- All LED lights include the power supply.
- Optional Occupancy Sensor shuts off after 30 minutes of inactivity and turns on immediately when re-entering the detection area.

## Height Adjustable Mechanisms

---

- Electric powered height adjustable mechanisms are offered on select units as noted in the Price List.
- Height adjustable mechanisms come factory installed and must be specified at the time of order.
- Center Drawer, ChargeSpot, 3/4 modesty panels and kneespace options are not available with the height adjustable mechanism.
- Maximum height is 42".
- Load capacity is recommended at a safe 50 lbs; weight distribution is key to capacity.
- Safety stop at 2" above the work surface prevents pinches.

## Height Adjustable Mechanisms (cont.)

---

- Height adjustable mechanisms reduce the kneespace depth by 9.5" and single pedestal desks have additional supports.
- Bridges, returns and credenzas will not have a standard grommet on back panel.
- Grommet not an option without vertebrae or box.
- Vertebrae and box options allow wire management from floor to worksurface.
- Optional Bluetooth allows user to sync the desk controls with a smartphone.
- Programmable control allows the user to program specific heights into the control unit.
- 5-year warranty.

## Sustainability

---

- 12 Year Warranty (some exclusion apply, see Full Warranty in Price List)
- Intertek's ETL Environmental VOC+ Product Certification
- ANSI/BIFMA Level 2 Certified
- Contribution to LEED V4
- CARB (The California Air Resources Board) Compliance Products
- Energy Efficient LED Task Lighting