

Encompass

Technical Specifications

General Information

- Encompass casegoods embrace workspaces with individual style and finesse at an affordable price.
- 14 carefully selected plain-sliced American Black Walnut, Maple and Cherry hardwood veneers available for both chassis and worksurfaces; 8 woodgrain laminate worksurface colors offer lasting beauty, superior resistance to normal wear, and easy maintenance.
- 18 pulls in Aluminum, Chrome & Black options
- 5 edge options
- Assembled components make specifications fast and easy.
- Rectangular, Bow Top, Corner, P-Top and D-Top desk options allow for a variety of product planning solutions to meet customer needs.
- Returns, Bridges & Credenzas in various configurations allow for optimal storage possibilities.
- Lateral Files, Hutches, Bookcases and Tables round out the series making it a clever solution for the budget-minded customer.
- NEMA Plug, Hardwired and Daisy Chain Power/Data Grommets are available in a variety of configurations.
- Custom capabilities.

Worksurface Construction

- Veneer tops are 1 5/32" thick and feature 5-ply balanced construction and feature a solid hardwood rim.
- Exposed surfaces are select grade cherry, maple and walnut veneers; Select grain patterns are used to maintain consistency and proper balance between units.
- Veneers feature a multi-step catalyzed finish, allowing for grain clarity, resistance to normal wear, and easy maintenance.
- Veneer tops are standard with a satin sheen finish.
- Laminate tops are 1 5/32" thick and feature 3-ply balanced construction and feature a solid hardwood rim. Exposed surfaces are high pressure laminate (HPL) with a black backer sheet.
- Worksurfaces are profiled on all four sides.
- Worksurfaces are bonded to the core with a PVA adhesive in a cold press to prevent separation of the laminate or veneer from the core.
- Grain direction runs left to right unless noted in Price List.
- Worksurfaces fit flush with adjoining worksurfaces.
- Returns, Bridges & Credenzas ship with flat brackets & screws to attach to adjoining worksurfaces.
- Grommets available for worksurfaces are 2 3/8" in diameter, have a low profile, and include an insert and cover.
- Grommets can be field or factory installed.
- Route power and data cables away from the worksurface through inherent grommet placement.
- Grommets may be ordered in the tops of all assembled desks, returns, bridges, credenzas, and component worksurfaces.
- Grommets are standard in the tops of corner units and extended corner units.
- Grommets will be black or silver based on pull color selected.

Drawer Construction

- All drawer fronts are 3-ply construction, 3/4" thick with matched wood grain.
- Drawer sides, back and front are wood grain vinyl wrapped, 1/2" thick.
- Box and file drawers have 1/8" thick hardboard bottoms; Lateral file drawers feature 1/4" thick bottoms.
- Drawers are 5-sided construction which allows for easy removal of the drawer fronts without disturbing the contents of the drawer.

Drawer Construction (Cont.)

- Drawer bottoms are placed in a Dado groove reinforced with hot melt glue that provides a consistent structure along the entire length of all sides of the drawer bottom.
- All drawers feature full extension, progressive action slides with precision steel ball bearings.
- All file drawers are standard with custom fitted filing systems designed to accommodate a variety of filing requirements.
- The custom fitted filing systems prevents folders from binding and allows the drawer to close with index tabs in place.
- File drawers have full height sides and metal file rails.
- All suspensions have a lifetime warranty.
- Letter width file drawers provide letter filing front to back, and letter or legal filing side to side.
- Lateral file drawers provide legal or letter filing front to back or side to side.
- Box and file drawers are tested for 100 lb capacity; Lateral files are tested for 200 lb capacity.

Component Construction

- Veneer chassis and storage components are securely fastened together using high quality European style fastening systems and heavy-duty 16-gauge joining brackets and wooden dowels to assure maximum strength.
- Heavy-duty adjustable glides with 1¼" of adjustment ensure proper leveling and compensate for uneven floors.
- Back panels on all units are inset into the sides so no raw edges are visible.
- All hinged doors include soft close hinges, unless otherwise noted; One piece hinge and base plate combination
- Soft close hinges reduce stress placed on the cabinet when the door is closed and offers a quiet closure.
- The height from the worksurface to the bottom of a surface mounted hutch is 23¾".
- Lateral File cabinets are equipped with an anti-tilt system which only allows one drawer to open at a time.
- Lateral file and hybrid storage cabinets are standard with central locking. Only one lock is required to lock all drawers. Door will have a separate lock that will match the drawers.
- Units with shelves are adjustable in 1¼" increments.
- Hutches are available in both surface mount and wall mount.
- All cabinet backs are fully finished with the exception of top units, wardrobes and bookcases
- Wardrobe and storage cabinets are the same height as a desk/return/credenza with a hutch.
- Drawer and Door fronts have vertically matched grain and utilize the same drawer construction as the pedestals.
- All desks, credenzas, returns, and files feature standard locking.
- Removable lock cores allow for re-keying in the field.
- All units ship randomly keyed standard, keyed alike available on request.
- All desks, returns, and credenzas (except lateral pedestals) have standard wire openings from inside the pedestal to the kneespace allowing quick access to technology below.
- Returns, bridge units, kneespace credenzas, and hutch units have standard grommets in back panels.
- Lock cores match pull color (silver or black).
- All desks, non-lateral credenzas, and returns have wire management access from pedestal to kneespace.
- Route power and data cables away from the worksurface through inherent grommet placement.
- Grommets will be black or silver based on pull color selected.
- Undersurface tracks are available for additional cord management.

Tack Boards

- Tackboards available in a wide variety of fabric selections for all hutch sizes including Momentum, Maharam, Mayer, CF Stinson, and DesignTex as well as others

Power & Data

- Power/Data Grommets are available in modular tops only.
- Duo Bezel Unit
 - › Recesses into worksurface for easy access to power and data.
 - › 2 power/2 USB ports
 - › Independent USB circuit controllers deliver up to 2.1 amps to each post.
 - › All mounting hardware included.
 - › FCC Part 15A and UL Approved for horizontal and vertical applications.
 - › NEMA Plug units include a 10' Power Cord.
 - › Hardwired units are 8 Wire/4 Circuit; Maximum 10 Duo units per circuit.
 - › Daisy Chain units allow up to 8 modules to be connected with available jumper cord.
- Trio Bezel Unit
 - › Recesses into worksurface for easy access to power and data.
 - › 3 power/2 USB/1 Open Data Port
 - › HDMI, VGA, or RJ45 Accessories sold separately.
 - › Independent USB circuit controllers deliver up to 2.1 amps to each post.
 - › All mounting hardware included.
 - › FCC Part 15A and UL Approved for horizontal and vertical applications.
 - › NEMA Plug units include a 10' Power Cord.
 - › Hardwired units are 8 Wire/4 Circuit; Maximum 10 Duo units per circuit.
 - › Daisy Chain units allow up to 8 modules to be connected with available jumper cord.
- Power Data Port
 - › Flip Top design retracts into worksurface to regain productive space.
 - › One-Touch access to power and data.
 - › (2) Power Outlets and (2) Open Ports for Data
 - › Water-Proof simplex outlets
 - › Includes a Voice/Data adapter kit to accept couplers and jacks when required.
 - › 6' Power Cord
- Chargespot
 - › Wireless Charging Enabled Devices (Qi) can be used directly with ChargeSpots without the Aid of a Spark.
 - › Not Compatible with Metal or Glass Surfaces.
- Chargespot Spark
 - › Apple Lightning compatible with Apple iPhones 5 and above
 - › Micro USB Compatible with Android, Windows and Blackberry Phones
 - › USBC are for newer Android Phones

Task Lighting

- Tasklights are available for factory or field installation.
- Tasklights are concealed by a valance.
- Tasklights are available in various sizes to match the length of the hutch.
- LED light
- Tasklights have a lens cover to reduce glare.
- Tasklights have an easily accessible on-off rocker switch.
- Jumper cords and occupancy sensors available.
- ETL listed and labeled

Task Lighting (cont.)

- All LED lights include the power supply.
- Optional Occupancy Sensor shuts off after 30 minutes of inactivity and turns on immediately when re-entering the detection area.

Sustainability

- 12 Year Warranty (some exclusion apply, see Full Warranty in Price List)
- Intertek's ETL Environmental VOC+ Product Certification
- ANSI/BIFMA Level 2 Certified
- Contribution to LEED V4
- CARB (The California Air Resources Board) Compliance Products
- Energy Efficient LED Task Lighting